



09/16/99

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.	991021	Total Pages	1c672 U.S. PTO 09/30/99 	
	First Named Inventor or Application Identifier				
	Masanori YACHI, Hiroshi ISHIKAWA and Yoshio SATOH				
	Express Mail Label No.				
Check Box, if applicable [] Duplicate					
APPLICATION ELEMENTS FOR:		ADDRESS TO:			
ACCELERATION SENSOR		Assistant Commissioner for Patents BOX PATENT APPLICATIONS Washington, D.C. 20231			
1. <input checked="" type="checkbox"/> Fee Transmittal Form (Incorporated within this form) (Submit an original and a duplicate for fee processing)					
2. <input checked="" type="checkbox"/> Specification Total Pages [26]					
3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) Total Sheets [8]					
4. <input checked="" type="checkbox"/> Oath or Declaration Total Pages [5]					
a. <input checked="" type="checkbox"/> Newly executed (original)					
b. <input type="checkbox"/> Copy from prior application (37 CFR 1.63(d) (for continuation/divisional with Box 17 completed).					
i. <input type="checkbox"/> <u>Deletion of Inventor(s)</u> Signed statement attached deleting inventor(s) named in prior application, see 37 CFR 1.63(d)(2) and 1.33(b).					
5. <input type="checkbox"/> Incorporation by reference (useable if box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.					
6. <input type="checkbox"/> Microfiche Computer Program (Appendix)					
7. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)					
a. <input type="checkbox"/> Computer Readable Copy					
b. <input type="checkbox"/> Paper Copy (identical to computer copy)					
c. <input type="checkbox"/> Statement Verifying identity of above copies					
<u>ACCOMPANYING APPLICATION PARTS</u>					
8. <input checked="" type="checkbox"/> Assignment Papers (cover sheet and document(s))					
9. <input type="checkbox"/> 37 CFR 3.73(b) Statement (when there is an assignee) <input checked="" type="checkbox"/> Power of Attorney					

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No. **991021**

First Named Inventor or Application Identifier

**Masanori YACHI, Hiroshi ISHIKAWA
and Yoshio SATOH**

PAGE 2 OF 3

10. ☐ English translation Document (if applicable)

11. ☒ Information Disclosure Statement ☒ Copies of IDS Citations (IDS/1449 w/ 3 refs.)

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)

14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
Status still proper and desired.

15. ☒ Claim for Convention Priority ☐ Certified copy of Priority Document(s)

- a. Priority of _____ application no. _____ filed on _____ is claimed under 35 USC 119.
The certified copies/copy have/has been filed in prior application Serial No. _____.
(For Continuing Applications, if applicable).

16. ☐ Other _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Division ☐ Continuation-in-part (CIP) of prior application no. ____/____

FEE TRANSMITTAL	Number Filed	Number Extra	Rate	Basic Fee
The filing fee is calculated below				\$760.00
Total Claims	18 - 20		x \$18.00	
Independent Claims	3 - 3		x \$78.00	
Multiple Dependent Claims			\$260.00	
Basic Filing Fee				760.00
Reduction by 1/2 for small entity				
Fee for recording enclosed Assignment			\$40.00	40.00
TOTAL				\$800.00

**UTILITY PATENT
APPLICATION TRANSMITTAL**

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No.

991021

First Named Inventor or Application Identifier

**Masanori YACHI, Hiroshi ISHIKAWA
and Yoshio SATOH**

PAGE 3 OF 3

☒ [XX] A check in the amount of \$800.00 is enclosed to cover the filing fee of \$760.00 and the assignment recordation fee of \$40.00.

☐ [] Please charge our Deposit Account No. **01-2340** in the total amount of _____ to cover the filing fee and the _____ assignment recordation fee. A duplicate of this sheet is attached.

☒ [XX] The Commissioner is hereby authorized to charge payment for any additional filing fees required under 37 CFR 1.16 or credit any overpayment to Deposit Account No. **01-2340**. A duplicate of this sheet is attached.

18. CORRESPONDENCE ADDRESS


**ARMSTRONG, WESTERMAN, HATTORI
MCLELAND & NAUGHTON
1725 K Street, N.W. Suite 1000
Washington, D.C. 20006
Telephone: (202) 659-2930
Facsimile: (202) 887-0357**

SUBMITTED BY

Typed or Printed Name **William G. Kratz, Jr.**

Reg. No. **22,631**

Signature



Date: **September 16, 1999**

WGK/yap

TITLE OF THE INVENTION

ACCELERATION SENSOR

BACKGROUND OF THE INVENTION

5 The present invention relates to an acceleration sensor and more particularly concerns an acceleration sensor that detects an acceleration in one direction (acceleration in linear motion).

10 Conventionally, small-size acceleration sensors of various types for detecting acceleration have been put into practical use. For example, with respect to cantilever-type acceleration sensors, the following acceleration sensors have been known: those having a construction in which a piezoelectric element is cantilevered and supported by a support member so that a voltage caused by a distortion in
15 the piezoelectric element in response to a generated acceleration is sensed and the acceleration is consequently detected; and those having a construction in which a semiconductor is cantilevered and supported by a support member so that a change in resistivity due to a distortion in
20 the semiconductor in response to a generated acceleration is sensed and the acceleration is consequently detected. Moreover, other acceleration sensors have been proposed in which the inertia of an optical fiber gyro is utilized so as
25 to detect an acceleration.

In the case of the above-mentioned cantilever-type acceleration sensors, in order to distort the structural element (piezoelectric element or semiconductor), it is necessary to increase the mass of the structural element so as to obtain a greater stress. Therefore, in order to enhance the detection precision, it is inevitable to make the acceleration sensors heavier and bulkier. Moreover, in the case of the acceleration sensor using an optical fiber gyro, when the diameter of the optical fiber is made smaller in an attempt to make the acceleration sensor smaller, the detection precision tends to deteriorate. Furthermore, since it is not possible to separate an acceleration in one direction and a rotation angular velocity by using a single acceleration sensor, there are still some problems to be solved before this is put into practical use.

BRIEF SUMMARY OF THE INVENTION

One objective of the present invention is to provide a small-size acceleration sensor which can detect an acceleration in one direction with high precision.

Another objective of the present invention is to provide an acceleration sensor which can separate an acceleration in one direction and a rotation angular velocity by using only a single sensor so as to detect the acceleration in one direction accurately.

Still another objective of the present invention is to provide an acceleration sensor which can detect accelerations in the respective three-dimensional directions at the same time.

5 The acceleration sensor in accordance with the first aspect of the present invention is provided with a vibrator, a weight portion that is connected to the vibrator, and supported at a position different from the center of gravity of the vibrator plus its own structure, and a detecting
10 section which detects the amount of characteristic corresponding to an angular moment that is exerted in the vibrator upon application of an acceleration in one direction to the vibrator and the weight portion.

FIG. 1 is an explanatory drawing that shows the
15 detection principle of the acceleration sensor of the present invention. The acceleration sensor of the present invention has a vibrator 1, a weight portion 2 connected thereto, and a detecting section 3. The weight portion 2 is supported at a supporting point S, and the position of this supporting point
20 S is different from the position of the center of gravity G of the vibrator 1 and the weight portion 2. When such an acceleration sensor is subjected to an acceleration in one direction (in the void arrow direction of FIG. 1), an angular moment centered on the supporting point S (arrow A, size MLa
25 in FIG. 1 (where M: mass of the weight portion 2, L: distance

from the supporting point S to the center of gravity of the weight portion 2, a: applied acceleration)) is exerted. A torsional deflection (arrow B in FIG. 1) is exerted in the vibrator 1 by this angular moment. The detecting section 3
5 detects the amount of characteristic corresponding to this angular moment. Since the size of the angular moment is proportional to the size of the acceleration of a detection target, it is possible to detect the acceleration by detecting the amount of characteristic.

10 In the acceleration sensor in accordance with the second aspect which has the same construction as the first aspect, the vibrator is provided as a torsion vibrator made by a piezoelectric element, and the amount of characteristic is provided as a voltage in the torsion vibrator corresponding
15 to the angular moment. The torsion vibrator of the piezoelectric element is used as the vibrator, and a difference in output voltages corresponding to the angular moments is sensed so that the acceleration is detected. Thus, it is possible to achieve a vibrator having a simple
20 structure.

The acceleration sensor in accordance with the third aspect is provided with a vibrator, a weight portion that is connected to the vibrator, and supported at a position different from the center of gravity of the vibrator plus its
25 own structure, and a detecting section which detects a

Coriolis force that is caused by a rotation angular velocity exerted in the vibrator upon application of an acceleration in one direction to the vibrator and the weight portion while the vibrator is vibrating in a constant direction. When the vibrator is subjected to an acceleration in one direction while being vibrated, the angular moment generates a rotation angular velocity in the vibrator, and the rotation angular velocity results in a Coriolis force that is orthogonal to the vibration direction of the vibrator. The acceleration is detected by sensing this Coriolis force. Thus, it becomes possible to detect the acceleration with a simple construction.

In the acceleration sensor in accordance with the fourth aspect which has a construction similar to the third aspect, the rotation axis of the rotation angular velocity is set in the same direction as the detection axis of the Coriolis force. Since the rotation axis of the rotation angular velocity is set in the same direction as the detection axis of the Coriolis force, the Coriolis force, which is caused by the rotation angular velocity exerted in the vibrator due to the angular moment, is accurately detected so that it becomes possible to improve the detection precision for acceleration.

In the acceleration sensor in accordance with the fifth aspect which has the same construction as the third aspect, at least one portion of the weight portion is formed as an

elastic member. Since at least one portion of the weight portion is an elastic member, it is possible to increase the rotation angular velocity exerted by the angular moment.

The acceleration sensor in accordance with the sixth aspect is provided with a first sensor which has a first vibrator supported at a position, with the center of gravity thereof being different from the position at which the first vibrator is supported, in which, upon application of an acceleration in one direction, a rotation angular velocity is exerted in the first vibrator; and a second sensor which has a second vibrator supported at a position, with the center of gravity thereof being the same as the position at which the second vibrator is supported, in which, upon application of an acceleration in one direction, no rotation angular velocity is exerted in the second vibrator, and a differential detector which detects a difference between outputs of the first sensor and the second sensor. Thus, the difference is detected between the output of the first sensor that has the supporting position and the center of gravity different from each other so as to generate a rotation angular velocity corresponding to an acceleration in one direction in the first vibrator and the output of the second sensor that has the supporting position and the center of gravity coincident with each other so as to generate no rotation angular velocity corresponding to an acceleration in

one direction in the second vibrator. The output of the first sensor contains a component corresponding to the rotational motion of the entire system and a component corresponding to the acceleration in one direction, while the output of the second sensor contains only the component corresponding to the rotational motion of the entire system. Therefore, by detecting the difference between the output of the first sensor and the output of the second sensor, only the component corresponding to the acceleration in one direction can be detected; therefore, even if the entire system is rotating, the acceleration in one direction can be detected accurately by using a single acceleration sensor. Moreover, it becomes possible to separate the rotational motion of the entire system and a linear motion.

In the acceleration sensor in accordance with the seventh aspect which has a construction similar to the sixth aspect, the rotation axis of the rotation angular velocity of the first sensor and the rotation axis of the rotation angular velocity of the second sensor are set in the same direction. Since the rotation axis of the rotation angular velocity of the first sensor and the rotation axis of the rotation angular velocity of the second sensor are set in the same direction, it is possible to detect the component corresponding to the acceleration in one direction with high precision.

In the acceleration sensor in accordance with the eighth aspect which has the same construction as the sixth or seventh aspect, the characteristic of the first vibrator and the characteristic of the second vibrator are made coincident with each other. Since the characteristics (sensitivity, frequency response, etc.) of the first and second sensors are made coincident with each other, the same components are detected with respect to the component corresponding to the rotational motion of the entire system; thus, it becomes possible to detect the component corresponding to the acceleration in one direction with high precision.

In the acceleration sensor in accordance with the ninth aspect which has a construction similar to that of any one of the sixth, seventh or eighth aspect, a plurality of sets each of which consists of the first sensor, the second sensor and the differential detector are provided.

In the acceleration sensor in accordance with the tenth aspect which has a similar construction to the ninth aspect, three sets each of which consists of the first sensor, the second sensor and the differential detector are provided, and these sets are arranged so that the detection directions for acceleration in the respective sets are made orthogonal to each other.

In the case when two sets each of which consists of the
25 first sensor, the second sensor and the differential detector

are installed in a manner so as to align their detection axes orthogonal to each other, accelerations in linear motions in the two-dimensional directions can be simultaneously detected on a plane, and in the case when three sets thereof are
5 installed with their detection axes being orthogonal to each other, accelerations in linear motions in the three-dimensional directions can be simultaneously detected in three dimensions.

The above and further objects and features of the
10 invention will more fully be apparent from the following detailed description with accompanying drawings.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is an explanatory drawing that shows the
15 detection principle of an acceleration sensor of the present invention.

FIG. 2 is a perspective view that shows the construction of an acceleration sensor in accordance with the first embodiment.

20 FIG. 3 is a perspective view that shows the construction of a vibrator (torsion vibrator) in the first embodiment.

FIG. 4 is a front view that shows the construction of an acceleration sensor in accordance with the second embodiment.

FIG. 5 is a perspective view that shows the construction
25 of the acceleration sensor in the second embodiment.

FIG. 6 is an explanatory drawing that shows a state of a tuning-fork-type vibrator at the time of detecting acceleration.

FIG. 7 is a schematic perspective view that shows the construction of an acceleration sensor in accordance with the third embodiment.

FIG. 8 is a schematic perspective view that shows the construction of an acceleration sensor in accordance with the fourth embodiment.

DETAILED DESCRIPTION OF THE INVENTION

Referring to Figures, the following description will discuss embodiments of the present invention.

(First Embodiment)

FIG. 2 is a perspective view that shows the construction of an acceleration sensor in accordance with the first embodiment of the present invention. This acceleration sensor is provided with a base 10 (3 mm in width, 8 mm in length and 0.7 mm in height) having a rectangular parallelepiped shape, a vibrator 11 (3 mm in width, 1.8 mm in length and 0.5 mm in height) having a rectangular parallelepiped shape that is constituted by a piezoelectric element made of, for example, 165Y-LiNbO₃, and a weight portion 12 (3 mm in width, 8 mm in length and 1 mm in height) having a rectangular parallelepiped shape made of, for

example, lead glass. The vibrator 11 is connected to an edge portion of the weight portion 12 with a face (3 mm \times 0.5 mm) of the vibrator 11 being made flush with a face (3 mm \times 1 mm) of the weight portion 12. The base 10 is joined to the weight portion 12 with their identical largest surfaces aligned face to face with each other, and the vibrator 11 is supported at an edge portion of the base 10. On the base 10, an output electrode 10a for drawing the output of the vibrator 11 and a GND electrode 10b used for connection to earth are installed.

FIG. 3 is a perspective view that shows the construction of the vibrator 11. The vibrator 11 is a torsion vibrator having two sliding vibrators 11a and 11b, and arranged so that a potential difference caused by sliding stresses (indicated by arrows in FIG. 3) having directions different from each other on the two sliding vibrators 11a and 11b is detected.

In such an acceleration sensor, upon application of an acceleration in one direction (in the direction of the void arrow of FIG. 2), an angular moment, centered on the supporting point of the vibrator 11, is exerted due to a positional offset between the center of gravity and the supporting point, with the result that each of the two sliding vibrators 11a and 11b of the vibrator 11 is subjected to lateral sliding in a different direction from each other.

Since a potential difference is exerted between the sliding vibrators 11a and 11b due to torsion vibration caused by the lateral sliding, the acceleration can be detected by sensing this potential difference by using the output electrode 10a.

5 Here, in the above-mentioned example, the torsion vibrator having the two sliding vibrators 11a and 11b is used as the vibrator 11; however, a torsion vibration tuning fork may be used as the vibrator 11. Moreover, if a longitudinal vibrator is used, it becomes possible to detect a stress due
10 to an angular moment in a longitudinal direction.

(Second Embodiment)

FIGS. 4 and 5 are front and perspective views that show the construction of an acceleration sensor in accordance with the second embodiment of the present invention. This
15 acceleration sensor is provided with a base 20 having a flat rectangular parallelepiped shape, and on the base 20 are installed a flat supporting portion 22 that is formed by an elastic member made of, for example, silicone rubber, and that is supported by a rubber member 21 in a manner so as to
20 stick out from the base 20, a gyro element 24 that is attached to the tip of the supporting portion 22 and contains a built-in tuning-fork-type vibrator 23, and a detector 25 for detecting a Coriolis force exerted in the tuning-fork-type vibrator 23.

25 FIG. 6 is an explanatory drawing that shows a state of

the tuning-fork-type vibrator 23 at the time of detecting an acceleration in such an acceleration sensor. During the acceleration detection, the tuning-fork-type vibrator 23 is always driven in one direction (in the void arrow direction of FIG. 6A) as shown in FIG. 6A. Upon receipt of an acceleration in one direction (in the void arrow direction of FIG. 4 and FIG. 5), an angular moment (rotation angular velocity) is exerted due to a positional off-set between the center of gravity and the supporting point. When such a rotation angular velocity is exerted, a Coriolis force (in the void arrow direction of FIG. 6B, size $F_c = 2mV\omega$ (m : the mass of the tuning-fork-type vibrator 23, V : vibration speed, ω : rotation angular velocity)) is exerted in a direction orthogonal to the vibrating direction. Thus, the acceleration is detected by sensing the Coriolis force by the use of the detector 25.

The rotation axis (arrow C in FIG. 5) of the angular moment (rotation angular velocity) caused by the acceleration and the detection axis (arrow D in FIG. 5) of the Coriolis force applied onto the tuning-fork-type vibrator 23 are set in the same direction so that the acceleration can be detected accurately by detecting the Coriolis force. Moreover, the elastic member is used as the supporting portion 22; therefore, in the case when the tuning-fork-type vibrator 23 is attached to the end of the supporting portion

22, as compared with the application of a rigid member as the supporting portion 22, even if an angular moment having the same size is exerted, a greater rotation angular velocity is generated, thereby making it possible to improve the sensitivity.

Here, in the above-mentioned example, the tuning-fork-type vibrator 23 is used; however, a prism-shaped vibrator or a column-shaped vibrator may be used as long as a Coriolis force is exerted in response to a rotation angular velocity. Moreover, although the supporting portion 22 is provided as an elastic member, a rigid member, supported by a spring, may be adopted. In the case of this construction, the tuning-fork-type vibrator 23 has a rotation angular velocity of the same size at any portion thereof.

(Third Embodiment)

In the case when the base supporting the tuning-fork-type vibrator is not allowed to rotate, the above-mentioned second embodiment makes it possible to detect an acceleration in one direction accurately. However, it is more likely that the base itself would rotate. In such a case, a Coriolis force due to such a rotation is also exerted in the tuning-fork-type vibrator; therefore, it is not possible to detect an accurate acceleration in one direction without separating the Coriolis force caused by the acceleration in one direction and the Coriolis force caused

by the rotation of the base. The following third embodiment gives an example in which the Coriolis forces of these two types are separated so that the acceleration in one direction can be detected accurately even if the base is allowed to rotate.

FIG. 7 is a schematic perspective view that shows the construction of an acceleration sensor in accordance with the third embodiment of the present invention. This acceleration sensor is provided with a base 30 having a flat rectangular parallelepiped shape; a first sensor 35 which has a flat supporting portion 32 that is formed by an elastic member made of, for example, silicone rubber, and that is supported by a rubber member 31 in a manner so as to stick out from the base 30, and a gyro element 34 that is attached to the tip of the supporting portion 32 and contains a built-in tuning-fork-type vibrator 33; a second sensor 39 which has a gyro element 38 that is secured to the base 30 by a metal member 36 and that contains a built-in tuning-fork-type vibrator 37; and a differential amplifier 40 which detects a difference between the output of the first sensor 35 and the output of the second sensor 39. The gyro element 34 of the first sensor 35 and the gyro element 38 of the second sensor 39 are set to have the same characteristics in the sensitivity to the rotation angular velocity, the frequency response, etc., and also have the same direction in the

detection axis (arrows E and F in FIG. 7) of Coriolis forces; thus, each of them exerts a Coriolis force having the same size in response to a rotation angular velocity having the same size.

5 The first sensor 35, which has the same construction as the acceleration sensor in the aforementioned second embodiment, has its positions of the supporting point and the center of gravity different from each other; therefore, an angular moment is exerted upon receipt of an acceleration in
10 one direction (in the void arrow direction in FIG. 7). In contrast, the second sensor 39 has its positions of the supporting point and the center of gravity coincident with each other; therefore, no angular moment is exerted even upon receipt of an acceleration in one direction.

15 Upon receipt of an acceleration in one direction (in the void arrow direction in FIG. 7) in a state where the base 30 is allowed to rotate, an angular moment (rotation angular velocity) is exerted in the first sensor 35 due to a positional off-set between the center of gravity and the
20 supporting point. Then, in the same manner as the second embodiment, a Coriolis force is exerted in the tuning-fork-type vibrator 33 due to the rotation angular velocity caused by the acceleration in one direction, and another Coriolis force is also exerted in the
25 tuning-fork-type vibrator 33 due to a rotation angular

velocity caused by the rotation of the base 30. An electric signal formed by adding these Coriolis forces of the two types is outputted to the differential amplifier 40.

In contrast, even upon receipt of an acceleration in one direction in a state where the base 30 is allowed to rotate, the second sensor 39 is not subjected to an angular moment (rotation angular velocity) due to the acceleration since the positions of the supporting point and the center of gravity are coincident with each other, and only the Coriolis force due to the rotational motion of the base 30 is exerted in the tuning-fork-type vibrator 37. The size of this Coriolis force is equal to the size of the Coriolis force caused by the rotational motion of the base 30 in the first sensor 35. Then, the electric signal corresponding to this Coriolis force is outputted to the differential amplifier 40 and other peripheral devices.

The differential amplifier 40 detects a difference between the output of the first sensor 35 and the output of the second sensor 39, and amplifies the difference to an appropriate size so as to output it. Therefore, the output from the differential amplifier 40 is allowed to exhibit only the Coriolis force caused by the acceleration in one direction, and the acceleration is detected by sensing this output. As a result, the state of a linear motion can be confirmed by the output of the differential amplifier 40,

while the state of a rotational motion can be confirmed by the output from the second sensor 39.

As described above, in the third embodiment, even if a rotational motion occurs in the entire system, the acceleration in one direction can be detected accurately. Moreover, types of motions can be classified into the linear motion and the rotational motion.

(Fourth Embodiment)

FIG. 8 is a schematic perspective view that shows the construction of an acceleration sensor in accordance with the fourth embodiment of the present invention. The fourth embodiment gives an example in which accelerations in the respective three dimensional directions (X-direction, Y-direction and Z-direction) are detected simultaneously.

In this acceleration sensor, three sets of acceleration sensors, each of which has the first sensor 35, the second sensor 39 and the differential amplifier 40 that have been explained in the third embodiment, are installed with their acceleration detecting directions arranged orthogonal to each other. In one set of the acceleration sensors, the first sensor 35 and the second sensor 39 have their detection directions for acceleration aligned in X-direction. In another set of the acceleration sensors, the first sensor 35 and the second sensor 39 have their detection directions for acceleration aligned in Y-direction, and in the other set of

the acceleration sensors, the first sensor 35 and the second
sensor 39 have their detection directions for acceleration
aligned in Z-direction. Here, the construction and operation
of each set of the acceleration sensors are the same as the
5 acceleration sensor in the third embodiment. Here, in FIG.
8, the differential amplifiers are omitted from the drawing.

With this arrangement, the linear acceleration in X-
direction, the linear acceleration in Y-direction and the
linear acceleration in Z-direction can be detected
10 simultaneously. Moreover, the linear motion and the
rotational motion can be recognized in three-dimensions.

As described above, in the present invention, the amount
of characteristic of an angular moment exerted on a vibrator
upon application of an acceleration in one direction is
15 detected so that the acceleration can be detected; therefore,
it becomes possible to detect the acceleration in one
direction with high precision by using a small-size
construction.

Moreover, upon application of an acceleration in one
20 direction, a Coriolis force due to the angular moment exerted
in the vibrator being vibrated is sensed so that the
acceleration can be detected; therefore, even if the entire
system is allowed to rotate, it is possible to detect the
acceleration in one direction accurately.

25 Furthermore, since three sets of the acceleration

sensors are installed with their detection directions being aligned orthogonal to each other, it becomes possible to simultaneously detect accelerations in the respective three-dimensional directions.

5 As described above, the acceleration sensor of the present invention makes it possible to detect an acceleration in a linear direction without the need for utilizing a stress distortion, and consequently to develop the application of the acceleration sensor to a new technical field.

10 As this invention may be embodied in several forms without departing from the spirit of essential characteristics thereof, the present embodiment is therefore illustrative and not restrictive, since the scope of the invention is defined by the appended claims rather than by
15 the description preceding them, and all changes that fall within metes and bounds of the claims, or equivalence of such metes and bounds thereof are therefore intended to be embraced by the claims.

[illegible]

a vibrator;

a detecting section which detects the amount of

2. The acceleration sensor according to claim 1, wherein

the vibrator is provided as a torsion vibrator made by a

3. The acceleration sensor according to claim 1, wherein

a vibrator;

a weight portion that is connected to the vibrator, and

of the vibrator plus its own structure; and

a detecting section which detects a Coriolis force that is caused by a rotation angular velocity exerted in the vibrator upon application of an acceleration in one direction to the vibrator and the weight portion while the vibrator is vibrating in a constant direction.

5. The acceleration sensor according to claim 4, wherein the rotation axis of the rotation angular velocity is set in the same direction as the detection axis of the Coriolis force.

6. The acceleration sensor according to claim 4, wherein at least one portion of the weight portion is formed as an elastic member.

7. An acceleration sensor for detecting an acceleration, comprising:

a first sensor having a first vibrator supported at a position, with the center of gravity thereof being different from the position at which the first vibrator is supported, wherein, upon application of an acceleration in one direction, a rotation angular velocity is exerted in the first vibrator;

a second sensor having a second vibrator supported at a position, with the center of gravity thereof being the same as the position at which the second vibrator is supported, wherein, upon application of an acceleration in one

direction, no rotation angular velocity is exerted in the second vibrator; and

a differential detector which detects a difference between outputs of the first sensor and the second sensor.

8. The acceleration sensor according to claim 7, wherein the rotation axis of the rotation angular velocity of the first sensor and the rotation axis of the rotation angular velocity of the second sensor are set in the same direction.

9. The acceleration sensor according to claim 7, wherein the characteristic of the first vibrator and the characteristic of the second vibrator are coincident with each other.

10. The acceleration sensor according to claim 8, wherein

the characteristic of the first vibrator and the characteristic of the second vibrator are coincident with each other.

11. The acceleration sensor according to claim 7, wherein

a plurality of sets each of which comprises the first sensor, the second sensor and the differential detector are provided.

12. The acceleration sensor according to claim 8, wherein

a plurality of sets each of which comprises the first sensor, the second sensor and the differential detector are provided.

13. The acceleration sensor according to claim 9, wherein

a plurality of sets each of which comprises the first sensor, the second sensor and the differential detector are provided.

14. The acceleration sensor according to claim 10, wherein

a plurality of sets each of which comprises the first sensor, the second sensor and the differential detector are provided.

15. The acceleration sensor according to claim 11, wherein

three sets each of which consists of the first sensor, the second sensor and the differential detector are provided, the sets being arranged so that the detection directions for acceleration in the respective sets are made orthogonal to each other.

16. The acceleration sensor according to claim 12, wherein

three sets each of which consists of the first sensor, the second sensor and the differential detector are provided, the sets being arranged so that the detection directions for

acceleration in the respective sets are made orthogonal to each other.

17. The acceleration sensor according to claim 13, wherein

three sets each of which consists of the first sensor, the second sensor and the differential detector are provided, the sets being arranged so that the detection directions for acceleration in the respective sets are made orthogonal to each other.

18. The acceleration sensor according to claim 14, wherein

three sets each of which consists of the first sensor, the second sensor and the differential detector are provided, the sets being arranged so that the detection directions for acceleration in the respective sets are made orthogonal to each other.

ABSTRACT OF THE DISCLOSURE

An acceleration sensor which has a vibrator, a weight portion that is connected to the vibrator, and supported at a position different from the center of gravity of the vibrator plus its own structure, and a detecting section which detects the amount of characteristic corresponding to an angular moment that is exerted in the vibrator upon application of an acceleration in one direction to the vibrator and the weight portion. When an acceleration in one direction is applied to the vibrator and the weight portion connected thereto, an angular moment is exerted in the vibrator due to the difference between the supporting point of the weight portion and the center of gravity of the vibrator plus the weight portion, and the amount of characteristic corresponding to the angular moment is detected by the detecting section so that the acceleration of a linear motion is detected.

FIG. 1





FIG. 2



(UNIT: mm)

FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7





FIG. 8



Declaration and Power of Attorney for U.S. Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ACCELERATION SENSOR

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日 に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)
外国での先行出願 Patent Application
10-265055 Japan

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

私、と、第35編米国法典119条(e)項に基づいて下記の米
国特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米
国特許出願に記載された権利、又は米国を指定している特許
協力条約365条(c)に基づき権利をここに主張します。また、
本出願の各請求範囲の内容が米国法典第35編112条
第1項又は特許協力条約で規定された方法で先行する米国特
許出願に開示されていない限り、その先行米国出願書提出日
以降で本出願書の日本国内または特許協力条約国際提出日ま
での期間中に入手された、連邦規則法典第37編1条56項
で定義された特許資格の有無に関する重要な情報について開
示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表
明が真実であり、かつ私の入手した情報と私の信じていること
に基づき、説明が全て真実であると信じていること、さらに故
意になされた虚偽の表明及びそれと同等の行為は米国法典第
18編第1001条に基づき、罰金または拘禁、もしくはそ
の両方により処罰されること、そしてそのような故意による
虚偽の表明を行えば、出願した、又は既に許可された特許
の有効性が失われることを認識し、よってここに上記のごと
く宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code,
Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent
or inventor's certificate, or 365(a) of any PCT International
application which designated at least one country other than the
United States, listed below and have also identified below, by
checking the box, any foreign application for patent or inventor's
certificate, or PCT International application having a filing date
before that of the application on which priority is claimed.

Priority Not Claimed
優先権主張なし

18/9/1998

(Day/Month/Year Filed)
(出願年月日)

☐

(Day/Month/Year Filed)
(出願年月日)

☐

I hereby claim the benefit under Title 35, United States Code,
Section 119(e) of any United States provisional application(s) listed
below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

I hereby claim the benefit under Title 35, United States Code,
Section 120 of any United States application(s), or 365(c) of any
PCT International application designating the United States, listed
below and, insofar as the subject matter of each of the claims of
this application is not disclosed in the prior United States or PCT
International application in the manner provided by the first
paragraph of Title 35, United States Code Section 112, I
acknowledge the duty to disclose information which is material to
patentability as defined in Title 37, Code of Federal Regulations,
Section 1.56 which became available between the filing date of the
prior application and the national or PCT International filing date of
application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own
knowledge are true and that all statements made on information
and belief are believed to be true; and further that these
statements were made with the knowledge that willful false
statements and the like so made are punishable by fine or
imprisonment, or both, under Section 1001 of Title 18 of the
United States Code and that such willful false statements may
jeopardize the validity of the application or any patent issued
thereon.

Japanese Language Declaration
(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。（弁理士、または代理人の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)
See list of attorneys and/or agents on page 5.

書類送付先

Send Correspondence to:

ARMSTRONG, WESTERMAN, HATTORI,
McLELAND & NAUGHTON
1725 K Street, N.W., Suite 1000
Washington, D.C. 20006

直接電話連絡先：（名前及び電話番号）

Direct Telephone Calls to: (name and telephone number)

Telephone: (202) 659-2930 Fax: (202) 887-0357

唯一または第一発明者名	Full name of sole or first inventor Masanori Yachi	
発明者の署名	Inventor's signature <i>Masanori Yachi</i>	Date August 27, 1999
住所	Residence Kawasaki-shi, Kanagawa, JAPAN	
国籍	Citizenship Japanese	
私書箱	Post Office Address c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, JAPAN	
第二共同発明者	Full name of second joint inventor, if any Hiroshi Ishikawa	
第二共同発明者	Second inventor's signature <i>Hiroshi Ishikawa</i>	Date August 27, 1999
住所	Residence Kawasaki-shi, Kanagawa, JAPAN	
国籍	Citizenship Japanese	
私書箱	Post Office Address c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, JAPAN	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

第三共同発明者		Full name of third joint inventor, if any Yoshio Satoh	
第三発明者の署名	日付	Third inventor's signature <i>Yoshio Satoh</i>	Date August 27, 1999
住所		Residence Kawasaki-shi, Kanagawa, JAPAN	
国籍		Citizenship Japanese	
私書箱		Post Office Address c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, JAPAN	
第四共同発明者		Full name of fourth joint inventor, if any	
第四発明者の署名	日付	Fourth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第五共同発明者		Full name of fifth joint inventor, if any	
第五発明者の署名	日付	Fifth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第六共同発明者		Full name of sixth joint inventor, if any	
第六発明者の署名	日付	Sixth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	

List of attorneys and/or agents

James E. Armstrong, III, Reg. No. 18,366; William F. Westerman, Reg. No. 29,988; Ken-Ichi Hattori, Reg. No. 32,861; Le-Nhung McLeland, Reg. No. 31,541; Ronald F. Naughton, Reg. No. 24,616; John R. Pegan, Reg. No. 18,069; William G. Kratz, Jr., Reg. No. 22,631; James P. Welch, Reg. No. 17,379; Albert Tockman, Reg. No. 19,722; Mel R. Quintos, Reg. No. 31,898; Donald W. Hanson, Reg. No. 27,133; Stephen G. Adrian, Reg. No. 32,878; William L. Brooks, Reg. No. 34,129; John F. Carney, Reg. No. 20,276; Edward F. Welsh, Reg. No. 22,455; Patrick D. Muir, Reg. No. 37,403; Gay A. Spahn, Reg. No. 34,978; John P. Kong, Reg. No. 40,054; and Luke A. Kilyk, Reg. No. 33,251.